



FT12 Mechanical



FT12 Pneumatic



FT12 Mechanical • FT12 Pneumatic

Machines on stand, foot or air operated, for tubular net closing or other tubular packing.

Specifications

- Fastener head angled at 30°, with adjustable height from 0.065 m to 0.565 m from work surface
- Fastener closure can be adjusted
- Fastener loading capacity: 740 sets or fasteners for 740 bags
- Machine weight: 38 kg
- Wide range of funnel sizes available (sold separately)
- Speed:
 - Mechanical FT12: 300-400 net bag/hour
 - Pneumatic FT12: 600-800 net bag/hour
- Air pressure required: 5 bar/70 lbs.
- Air consumption: 4,5 dm³/cycle at 6 bar/85 lbs.

Uses FT12 fasteners



For each net bag, the FT12 and FT30 machines use 2 fasteners and simultaneously cut the net.

Electric FT30 Packaging Machine

Electric machine on stand for faster tubular net closing or other tubular packing.

Specifications

- Stand rests on wheels for mobility
- Fastener head angled at 20°
- Adjustable height work surface
- Fastener closure can be adjusted
- Automatic trigger
- Fasteners made from 2 coils of strapping wire; makes 20,000 bags without reloading
- Capacity: 1,800 net bags/hour
- Electric powered 230-400 V Tri
- Machine weight: 105 kg
- Machine dimension: h x l x d
1130 x 560 x 900 mm
- Wide range of funnel sizes available (sold separately)
- Strapping wire (2.85 x 0.44 mm)
450 m long, weighs 4.5 kg each



FT30 Electric

